

ÖLFLEX® CLASSIC 100 H

Halogen-free power and control cable, oil-resistant and very flexible

ÖLFLEX® CLASSIC 100 H - halogen-free flexible cable, HFFR and oil-resistant. Power and control cable for various applications, CPR, nominal voltage 450/750V

Info

CPR: Article number choice under www.lappkabel.com/cpr



Torsion-resistant



Oil-resistant



Halogen-free



Flame-retardant



Cold-resistant

Benefits

Easy handling and installation due to very flexible design

Wide application range due to excellent product features

ÖLFLEX® CLASSIC 100 H

Application range

Public buildings like airports or railway stations

Plant construction, machine building

Heating and air-conditioning systems

Event equipment

Particularly where human and animal life as well as valuable property are exposed to a high risk of fire hazards

Suitable for torsional applications which are typical for the loop in wind turbine generators (WTG)

Product features

Flame-retardant according to IEC 60332-1-2

(flame spread on a single cable)

No flame propagation according to IEC 60332-3-24 or IEC 60332-3-25 (flame spread on vertical cable or conductor bunch)

Halogen-free according to IEC 60754-1

(amount of halogen acidic gas)

Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)

Low smoke density according to IEC 61034-2

Oil-resistant according to EN 50363-4-1 (TM5)

and UL OIL RES I and OIL RES II

Ozone-resistant according to EN 50396

Norm references / Approvals

Based on IEC 60227-5 and EN 50525-2-51

Based on EN 50525-3-11

Product Make-up

Fine-wire strand made of bare copper wires

Core insulation: Halogen-free

Sheath made of special halogen-free compound, grey (RAL 7001)

Technical Data

Classification:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Core identification code:	Coloured according to VDE 0293-308, see appendix T9
Conductor stranding:	Fine wire according to VDE 0295, class 5 / IEC 60228 class 5
Torsion movement in WTG:	TW-0 & TW-2, refer to appendix T0
Minimum bending radius:	Occasional flexing: 15 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage:	U ₀ /U: 450/750 V Fixed, protected installation: U ₀ /U: 600/1000 V
Test voltage:	4000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	Occasional flexing: -30 °C to +70 °C Fixed installation: -40 °C to +80 °C

ÖLFLEX® CLASSIC 100 H

Note

Unless otherwise specified, the product values shown are nominal values. You can receive further values, such as tolerances, upon request if they are available and have been released for publication.

Copper price basis: EUR 150/100 kg; see catalogue appendix T17 for the application and definition of "Metal price basis" and "Metal index"

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging: Ring ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred packaging (e.g. 1 x 500 m drum or 5 x 100 m rings)

Single lengths for dimensions: $\geq 4G50$ max. 500 m; $\geq 4G120$ max. 400 m

Photographs are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

**ÖLFLEX® CLASSIC 100 H**

Article number	Number of cores and mm ² per conductor	Outer diameter [mm]	Copper index (kg/km)	Weight (kg/km)
0014150	2 X 1.5	7.6	28.8	91
0014151	3 G 1.5	8.3	43.2	114
0014152	4 G 1.5	9	57.6	140
0014153	5 G 1.5	10.1	72	176
0014156	2 X 2.5	9	48	133
0014157	3 G 2.5	9.7	72	167
0014158	4 G 2.5	10.8	96	207
0014159	5 G 2.5	11.9	120	260
0014162	3 G 4	11.4	115.2	240
0014163	4 G 4	12.7	153.6	303
0014164	5 G 4	13.9	192	372
0014166	3 G 6	12.7	172.8	320
0014167	4 G 6	13.9	230.4	400
0014168	5 G 6	15.8	288	510
0014170	4 G 10	17.9	384	662
0014171	5 G 10	19.9	480	826
0014173	4 G 16	20.7	614.4	957
0014174	5 G 16	23	768	1193
0014176	4 G 25	25.4	960	1480
0014177	5 G 25	28.5	1200	1860
0014179	4 G 35	28.8	1344	1985
0014180	5 G 35	32.3	1680	2490
0014182	4 G 50	35	1920	2830
0014184	4 G 70	40	2688	3890
0014186	4 G 95	46	3648	5110
0014188	4 G 120	51	4608	6315

Last Update (17.06.2017)

©2017 Lapp Group - Technical changes reserved

Product Management www.lappkabel.deYou can find the current technical data in the corresponding data sheet:
PN 0456 / 02_03_16